

2A Water Curtain Stainless Steel

Water Wall/ Water Screen. In form of an illuminated, up to 30 metres high waterfall or an impressive projection surface. A high amount of nozzles and water create a homogeneous water-surface.

KEY FEATURES:

- free falling waterscreen with a big water amount up to 6000l/hour
- Indoor / Outdoor application
- Any rectangular format
- Water movement falling top down
- Standard segments with a length of 1m, 2m, 3m
- Number of segments unlimited
- Fully compatible with the 2.B Watercurtain curved
- Heights of up to 30m realisable
- Corresponds to BGV C.1 (Load above persons)
- Excellently capable for video, slide, back lights and laser projection
- No stripes in the picture visible
- No columns between the segments or nozzle plates
- 400 nozzles per metre
- Very great water amount of up to 6000 litre/hour/metre
- Simple maintenance and cleaning (High-grade steel, simple to demount)
- Quick and easy installation because of optimised components
- Also available for the use in chlorine water, swimming pools

OPTIONS:

- 2AS Shutter for fast shutdown of 330mm segments
- 2AC the first full watercurtain for ceiling mounting
- 2B Watercurtain curved. Fully compatible and therefore also useable as curve and circle in combination with 2A with 2A Segments for any free combination

Technical Requirements:

- Power connection 220V oder 400V 50Hz at the system (depending on the dimensions of the watercurtain)
- water connection 1/2" ,max. 20m distance (for exhibition and event use)
- water connection 1/2" ,max. 20 meter (for exhibition and event use)
- Trussing / attachment for the screen, approx. 70Kg/m



